



International Journal of Innovative Research in Computer and Communication Engineering

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Website: www.ijirccce.com

Vol. 5, Issue 11, November 2017

A Review of Different Approaches over MIMO Handover in LTE-OFDM Systems

Vimlesh Kumar¹, Prof. Shivnarayan Ahirwar²

M.Tech Scholar, Department of Electronics & Communication Engineering, OIST, Bhopal, M.P, India¹

Assistant Professor, Department of Electronics & Communication Engineering, OIST, Bhopal, M.P, India²

ABSTRACT: Long Term Evolution (LTE) is an updated form of 3G UMTS to meet the all the more requesting client necessities, for example, fast information get to and better Quality of Service (QoS). 3GPP standard acquaints handover system with meet the extra client necessity of taking care of consistent portability crosswise over various cell districts. Amid handover, there is a test to meet the better QoS particularly for constant administrations, for example, voice call. Handover happens all the more every now and again in fast portability. This is additionally the situation when end client is at the edge of the cell. In any case, there are distinctive procedures that exist to consider effective handover to occur without influencing the administration experienced by the end client. In this paper, we think about the design of LTE framework and overview the handover systems. So as to accomplish high information rate correspondence with versatility, Long Term Evolution (LTE) has been presented. LTE Downlink frameworks receive Orthogonal Frequency Division Multiple (OFDM) and MIMO to give upto 100 Mbps (expecting a 2x2 MIMO framework with 20MHz transmission capacity). The execution pick up of MIMO vigorously relies upon the exact estimation of Channel State Information (CSI), which is pivotal for each interchanges framework. In this paper, we display diverse channel estimation calculations for LTE Downlink frameworks. This incorporates channel estimation utilizing Pilot Symbols and Blind Channel estimation calculations. The estimation strategies included the Least Square Error (LSE) and the Minimum Mean Square Error (MMSE) is being examined lastly analyzed.

KEYWORDS: MIMO, LTE, OFDM, CSI, LSE, MMSE

I. INTRODUCTION

The raising requests for fast and solid remote interchanges have prodded improvement of different input-multiple-output (MIMO) frameworks with various radio wires at every transmitter and beneficiary sides. To effectively collect the ability and assortment increases realistic by MIMO channels, various space-time continuum process strategies have been produced, for example, Bell Labs layered space-time continuum models and orthogonal space-time continuum piece codes, to give some examples. To additionally upgrade the framework ability, data theoretic research demonstrates that an input channel can be used to give channel state data (CSI) to the source angle, which could affect shut circle capacity picks up essentially once the lucidness time of the MIMO channel is adequately expansive. At the point when brilliant criticism of CSI is inaccessible because of many-sided quality or utility limitations, the execution furthest reaches of MIMO frameworks under uproarious or quantized input are assessed in the investigation. Various input systems are conceived to comprehend the nearby circle capacity pick up. In control plans in view of quantized criticism information are intended to lessen an upper bound of numerous input-single-output (MISO) framework. At what time just the list of the most incredible pillar shaping vector is nourished back to the transmitter, the issue of quantized most flag to-clamor proportion (SNR) shaft framing is settled inside the examination. Under input connect capacity requirement, a half and half bar shaping and versatile power-control engineering is created in the investigation. For scalar power criticism and per-receiving wire vector control input, the issue of ideal MIMO interface limit is ascertained in the examination, while the issue of ideal MIMO multiuser configuration is tackled in the investigation in. As of late, two point by point type of fragmentary criticism, particularly, channel mean input (CMF) and channel covariance input (CCF), incorporate be explore for moderate differing and rapidly changing MIMO channels, separately. In light of CMF, ideal multiantenna communicate precoder design has been seek after in the investigation, while with CCF, a required and sufficient condition for the optimality of beam shape is gotten in the examination. The



International Journal of Innovative Research in Computer and Communication Engineering

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Website: www.ijirccce.com

Vol. 5, Issue 11, November 2017

blunder execution of versatile regulation with deferred reaction, least mean square mistake (MMSE) channel forecaster, and communicate shaft shaping is explored in the investigation. As per the writing, the pilot image helped balance has as of late risen as a promising MIMO estimator utilized for time-shifting remote correspondence frameworks. It offers attractive introduction with viable registering many-sided quality. In this way, the utilization of PSAM approach perform channel deduction is prescribed here for handy setting. In this exertion, an execution investigation of the novel pilot image helped adjustment framework chipping away at MIMO channels and TCM-STBC codes are investigated. Here are two for the most part characterized TCM classes: the anticipated TCM and the multidimensional trellis coded adjustment which is known to give high transmission capacity effectiveness. In this paper, we concentrate on the execution investigation of the second sort of TCM as an external code. We consider here on the perceived four multidimensional TCM (4D-TCM) plot depicted in which offers high information rate.

II. LITERATURE REVIEW

A wide An extensive variety of research techniques is utilized for divert estimation in LTE-OFDM is introduced here. The assessed works are group the diverse channel estimation techniques like pilot based, daze channel, LMS and RLS, LS and MMSE and other channel estimation strategies.

Emna Ben Slimane et. al. [1] "Pilot Assisted Channel Estimation in MIMO-STBC System Over Time-Varying Fading Channels" In this anticipated work challenges about the arrangement of direct state data in various information and different yield (MIMO) framework base on space time piece codes (STBC) on moderate time-changing Rayleigh blurring channels are address. We built up a novel MIMO channel estimation calculation to embrace a pilot image helped tweak (PSAM) which has been ended up being useful for blurring channels. In this propel, pilot images are an ideal opportunity to time embedded into the information stream that is sent by the orthogonal STBC encoder. At the recipient point, we plan an essential MIMO channel estimation technique past to being utilized by STBC decoder. right and direct PSAM estimation strategy is expected for MIMO in view of orthogonal STBC codes. The transmitter simply embed known ideally and similarly paced pilot image in information data piece. The join flag is coded by utilizing orthogonal STBC code. The transmitted flag is defiled by added substance clamor and moderate blurring. The moderate blurring channel is demonstrated by the Jakes show; it is additionally been enduring over the STBC codeword stage. The recipient assess and introduces the channel limit gave by pilot images with a specific end goal to accomplish the sufficiency and the stage reference for location. Reproduction result demonstrate that channel estimation base on PSAM strategy is right in wording BER for both MIMO plans. The benefit of this procedure is its accomplishment ease notwithstanding the aggressive execution. It is additionally demonstrated that estimation strategy is ideal for moderate time-changing blurring channels and can be reached out to quick time-fluctuating blurring channels.

Twosome Zhang, et. al. [2] "On the cutoff points of Feedback Rates for Pilot-Assisted MIMO Systems" For pilot-help different info numerous yield (MIMO) framework with deficient input, we inspect the relationship in the middle of the criticism transmission rate and coming about pick up of shut circle limit. In view of this relationship evaluate by rate-twisting hypothesis, we analyze the upper and lower limits of the input rate that would influence pick up of positive shut circle limit without unreasonably devouring criticism transmission assets. across the board recreations are complete to approve the diagnostic outcome and to reveal insight into the achievable shut circle MIMO limit given the framework plan parameterized by the quantity of radio wires, pilot control designation, transmit motion to-commotion proportion, and limited input rate. These outcomes give rule on the input channel for noteworthy plans of valuable pilot-helped MIMO frameworks. For functional correspondence outline with pilot-helped MIMO handsets and CSI criticism, we have lead investigation and reproductions to address the effect of input rates on shut circle criticism picks up. Given the framework parameters including the quantity of recieving wires, pilot control assignment and transmit SNR, we need to infer the scientific relationship interfacing input rate to shut circle limit pick up, which thusly prompts the lower and upper limits of the criticism rate for taking up in reasonable usage.

Jyoti P. Patra et. al. [3] "A Comb-Type Pilot Symbol Aided Channel Estimation for the STBC based OFDM System over Frequency Selective Channel" In this paper, the channel estimation technique for space time square code (STBC) in light of multi-input multi-yield (MIMO) orthogonal recurrence division multiplexing (OFDM) is examine for multipath blurring channels. The channel estimation depends on brush sort pilot game plan where's the pilot subcarriers are put at difine interim of each OFDM image piece and are orthogonal between vary transmitting radio



International Journal of Innovative Research in Computer and Communication Engineering

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Website: www.ijirccce.com

Vol. 5, Issue 11, November 2017

wires in light of the fact that the benefits of orthogonal pilot subcarrier, the genuine transmitted flag is totally recuperate from the blended exchanged flag on the recipient side. The minimum square calculation is received for appraisal of channel at pilot subcarrier while the interjection is finished at information subcarrier. The execution of the create channel estimation strategy is contrast and the perceived single-input single-yield (SISO) OFDM framework in light of image mistake rate (SER). The reenactment comes about demonstrates that the STBC OFDM gives enhanced execution than SISO OFDM and the SER diminishes with the flag to commotion proportion (SNR) and the quantity of get reception apparatus increments. Pilot helped channel estimation strategy utilizing brush sort pilot game plan with various interjection technique for STBC based OFDM framework is researched w multipath blurring channel. The orthogonal properties of the pilot game plan have been depicted in an awesome detail. Because of the orthogonal pilot game plan between the two transmitting radio wires, the channel estimation method is basic and low computational cost as no lattice reversal is required. The recreation comes about demonstrates that brush sort pilot with spline and low-pass interjection method of STBC-OFDM framework performs superior to the customary OFDM framework. From the recreation result, plainly low-pass addition outflank than spline sort interjection strategy.

Mohamed Marey, et. al [4] "Dazzle STBC Identification for Multiple-Antenna(MA) OFDM Systems" The issue of space time piece distinguishing proof for different radio wire orthogonal recurrence division multiplexing (FDM) frameworks working over recurrence specific channels without precedent for writing. Past examinations accessible on the subject of STBC ID were restricted to single-bearer frameworks working on recurrence level channels. OFDM frameworks make this subject all the more difficult to deal with since the identifiers works in recurrence specific channels with nearly nothing or without information of the start of the OFDM squares, recurrence particular channel coefficients.

Leandro D'Orazio, et.al.[5] "MMSE Multi User Detection with GA-helped Channel Estimation for STBC MC-CDMA Mobile Communication Systems" MIMO MC-CDMA method have been arranged keeping in mind the end goal to build framework limit through recurrence particular remote channels. The key normal for MIMO MC-CDMA is the capability of abusing range together in time, space and recurrence areas. Specifically, Alamouti's coding plan has been anticipated as an exceptionally basic and logically rich instrument with a specific end goal to put without hesitation space-time piece coding. The primary trouble to be tended to will be to productively recombine assortment keeping in mind the end goal to accomplish the best execution within the sight of multi-client impedance.

Citation	Title	Journal Name/Year	Research scope
[1]	Pilot Assisted Channel Estimation in MIMO-STBC System Over Time-Varying Fading Channels	IEEE International Workshop on Resource Allocation 2016	In it a accurate and straightforward PSAM estimation method is proposed for MIMO based on Orthogonal STBC codes.
[2]	On the limits of Feedback Rates for Pilot-Assisted MIMO Systems	IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY June 2015	In this results provide guideline on the feedback channel for meaningful designs of practical pilot-assisted MIMO



International Journal of Innovative Research in Computer and Communication Engineering

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Website: www.ijircce.com

Vol. 5, Issue 11, November 2017

			systems.
[3]	A Comb-Type Pilot Symbol Aided Channel Estimation for the STBC based OFDM System over Frequency Selective Channel	IEEE Asia Pacific Conference 2013	In it comb type pilot arrangement with different interpolation method for STBC based OFDM system is Investigated over multipath fading channel.
[4]	Blind STBC Identification for Multiple-Antenna(MA) OFDM Systems	IEEE TRANSACTIONS ON COMMUNICATIONS, May 2014	A novel STBC-OFDM identification method is proposed.
[7]	Training-Based MIMO Channel EstimationA Study of Estimator Tradeoffs and Optimal Training Signals	IEEE TRANSACTIONS ON SIGNAL PROCESSING, MARCH 2006	The performance of several training-based MIMO channel estimation is realize

III. METHOD

A. STBC BASED OFDM SYSTEM MODEL

The framework display for STBC-OFDM with two transmission radio wire and a get recieving wire is appeared in the Fig1. then again, the framework model can be reached out to any no.of transmitting and getting reception apparatuses to get high transmit decent variety. At the transmitter end, the information succession is produce and balance as per any positive tweak plan, for example, QPSK, BPSK or 16QAM. After this the yield balanced information is gone through STBC encoder. The STBC encoder use to change the single information adjusted data information into two parallel encoded yield information by utilizing Alamouti STBC plot. The pilot grouping is additionally produced and regulates comparably to the information succession. After that both encoded information and pilot subcarrier go by the serial to parallel converter lastly came to at the (IFFT) Inverse Fast Fourier Transformation piece. The yield of the IFFT square communicated as

$$x_{t,n}^{\beta} = \sum_{k=0}^{N-1} X_{t,k}^{\beta} e^{j2\pi kn/N}$$

$$\beta = 1, 2, \quad n, k = 0, 1, 2, \dots, N - 1 \quad (1)$$

International Journal of Innovative Research in Computer and Communication Engineering

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Website: www.ijirccce.com

Vol. 5, Issue 11, November 2017

Where data vector denotes by $X_{t,k}^\beta, x_{t,n}^\beta$ before and after of the IFFT block, β denote the transmitting antenna index, and n, k represents the k th subcarrier and the its n th time instant at the t th symbol period. Where N denote the total number of OFDM data subcarrier. at last, the resulting signals are transmitted from the antennas following insertion of the cyclic prefix (CP) which is assumed to be largas compare to the delay spread of the multipath channel to avoid inter symbol interferences (ISI).The channel is assumed to be static or quasi-static for two time slot of STBC block . The channel model use in this paper is describe latter in this segment. The received signal can be obtain by taking the difficulty of transmitted data signal with the channel impulse reaction and can be expressed in term as

$$r_{j,t,n} = \sum_{l=0}^{L-1} h_{j,t,l}^\beta x_{t,n-l}^\beta + w_{j,t,n} \quad (2)$$

$H_{j,t,k}^\beta$ denote the frequency response of the channel from β th transmitting antenna to the j^{th} receiving antenna and on the k^{th} subcarrier. N_t and N_r represent the quantity of transmit and receive antennas. $w_{j,t,k}$ Is the additive white Gaussian noise with zero mean and unit variance. After the processed signal is decoded by the STBC decoding method. to conclude, the transmitted signal is recovers after taking the hard resolution of the decoded signal. In this paper, IEEE802.11 model with exponential power delay profile is adopted. The channel is modeled as finite impulse response




Figure 1 Block diagram of an STBC-OFDM system model.

IV. CONCLUSION

In this paper, essential idea of OFDM, MIMO and LTE physical layer are clarified. Different channel estimation methods for LTE downlink framework are examined and after that analyzed. For that distinctive past procedures and calculations are checked on. From every one of these audits it can be reasoned that MMSE technique is superior to LS strategy, however at the cost of computational many-sided quality. Delicate handover systems guarantee to be better treatment of the administration irregularity related with the hard handover. A large portion of the exploration works make utilization of keeping up different associations one with every controller. This has the preferred standpoint yet at the cost of the portable station transmission control. The pilot supported channel estimation method by utilizing brush sort pilot course of action with contrast introduction system for STBC based OFDM plot is explored over multipath blurring channel. The orthogonal properties of pilot game plan have been depicted in a substantial detail. Cause to the orthogonal pilot game plan in the two transmitting radio wires, the channel estimation system is basic and low



ISSN(Online): 2320-9801
ISSN (Print) : 2320-9798

International Journal of Innovative Research in Computer and Communication Engineering

(A High Impact Factor, Monthly, Peer Reviewed Journal)

Website: www.ijirccce.com

Vol. 5, Issue 11, November 2017

calculation cost on the grounds that no grid reversal is vital. The reenactment comes about demonstrate the brush sort pilot with spline and low-pass interjection procedure of STBC-OFDM plot performs superior to the typical OFDM framework. From the recreation result, clear that the low-pass insertion beat than spline sort interjection process. We can see that SER diminish as number of accepting radio wire increments. The created channel estimation has a disappointment of 2dB to 2.5dB SNR when contrasted with the model situation where it is expected that the ideal channel learning is known at the less than desirable end. So that from the recreation results and hypothesis, it is demonstrated that created channel estimation method is best appropriate for the channel estimation reason for multipath blurring channel.

REFERENCES

- [1] Jin-Taek Lim and Dong-Ho Cho, "Gain Analysis of Adaptive MIMO Semisoft in LTE-OFDM Systems" 978-1-4799-8088-8/15/\$31.00 201 5 IEEE.
- [2] Duo Zhang, Guo Wei, Jinkang Zhu, Zhi Tian, " On the Bounds of Feedback Rates for Pilot-Assisted MIMO Systems" IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, VOL. 56, NO. 4, JULY 2007.
- [3] Jyoti P. Patra, Poonam Singh, " A Comb-Type Pilot Symbol Aided Channel Estimation for STBC based OFDM System over Frequency Selective Channel" 978-1-4799-2751-7/13/\$31.00 ©2013 IEEE
- [4] Mohamed Marey, Octavia A. Dobre, Robert Inkol, "Blind STBC Identification for Multiple-Antenna OFDM Systems" IEEE TRANSACTIONS ON COMMUNICATIONS, VOL. 62, NO. 5, MAY 2014 0090-6778/14\$31 2014 IEEE
- [5] Leandro D'Orazio, Claudio Sacchi, Massimo Donelli, Francesco G.B. De Natale, " MMSE Multi-User Detection with GA-assisted channel Estimation for STBC MC-CDMA Mobile Communication Systems" 978-1-4244-2204-3/08/\$25.00 ©2008 IEEE
- [6] V. Tarokh, H. Jafarkhani, and A. R. Calderbank, "Space-time blockcodes from orthogonal designs," IEEE Trans. Inf. Theory, vol. 45, no. 5, pp. 1456-1467, Jul. 1999.
- [7] M. Biguesh and A. B. Gershman, "Training-based MIMO channel estimation: A study of estimator tradeoffs and optimal training signals," IEEE Trans. Signal Process., vol. 54, no. 3, pp. 884-893, Mar. 2006.
- [8] J.K. Cavers, "An Analysis of Pilot Symbol Assisted Modulation for Rayleigh Fading Channels," IEEE Trans. on Veh. Tech., vol. 40, no.4, pp. 686-693, Nov. 1991. S. Ohno and G. B. Giannakis, "Average-rate optimal PSAM transmissions over time-selective fading channels," IEEE Trans. Wireless Commun., vol. 1, no. 4, pp. 712-720, Oct. 2002.
- [9] K. Yu, I. Evans, and I. Collings, "Performance analysis of pilot symbol aided QAM for Rayleigh fading channels," in Proc. IEEE ICC, New York, NY, pp. 1731-1735, May 2002.
- [10] S.S. Ikki, S. Al-Dharrab and M. Uysal, "Error Probability of OF Relaying with Pilot-Assisted Channel Estimation over Time-Varying Fading Channels," IEEE Transactions on Vehicular Technology, vol.61,no. 1,393 - 397,2012.
- [11] Wenyu Li, Yunfei Chen and Norman C. Beaulieu, "BER Optimization of Pilot Symbol Assisted MRC PSAM for Slow Fading Channels " IEEE Communications Letters, vol. 13, no. 12, December 2009.
- [12] Eiji Okamoto, Huan-Bang Li, and Tetsushi Ikegami, "A Pilot Symbol Assisted Compensation Scheme of Fading and Frequency Offset for 16QAM," IEEE International Conference on Universal Personal Communications (ICUPC), vol. 2, pp. 921 - 924, 2008.