



# **Energy Consumption Mechanism in Data-Gathering Wireless Sensor Networks**

Nilesh V. Wanare, Kanchanvarpe

M.E., Dept. of Computer, RMD Sinhgad School of Engineering, Pune, India

Assistant Professor, Dept. of Computer, RMD Sinhgad School of Engineering, Pune, India

**ABSTRACT:** In Wireless sensor networks, the sensors are attached with the devices to monitor their performance and data. The Wireless sensor network, the energy consumed by the resources are measured across the remote location(base stations).There are various performance metric used like network lifetime to evaluate battery powered sensor nodes.These nodes transfer the data packets from one station to another. Due to energy hole in wireless sensor network, the whole network gets disabled. This system determines the boundary of energy hole in data gathering wireless sensor network and estimate the traffic load, energy consumption and lifetime of sensor nodes during the entire network lifetime. Thissystem defines the analytical model to balance the energy consumption and improve the network lifetime.

**KEYWORDS:** Energy efficiency, energy hole, network lifetime, routing, wireless sensor network.

## **I. INTRODUCTION**

In proposed system we modulate problem of energy hole evolution for effective data acquisition We design sensor network by appropriate sensor deployment, Such sensor networks are implemented to collect multiple data points from each selected location over a period of weeks or months. Battery capacity gain by sensor nodes is limited in computation capability, memory space, communication bandwidth and also energy supply. So to improve the operational lifetime of a sensor network is critical. A wireless sensor network consists of a set of sensing devices which work to collect data from a sensor deployed area. The limited energy available at the sensors makes the network lifetime one of the most critical issues in the design of WSNs. A information sensing in WSN consists of a large number of battery powered sensor nodes that sense the allocated bandwidth limitation and periodically send the sensing results to the sink.The nodes near to the sink need to transfer the data packets from other nodes; they exhaust their energy quickly, leading to an energy hole around the sink. So that complete wireless sensor network fail to transmit data packet.Energy hole is crucial and challenging for lifetime analysis in WSNs, because it can lead to a premature death of the network. First prove that the energy hole problem is inevitable in the WSN under some specific conditions. Analyze in what condition the energy holes could appear. Discuss the load balancing techniques to mitigate energy hole problem in large-scale WSNs and propose a distributed heuristic solution to balance the energy utilization of sensor nodes by adjusting the transmission power. The energy hole crisis also been studied in cluster-based WSNs .Most of the existing works suppose that energy hole locates around the sink, and design energy-efficient routing protocols to mitigate the unbalanced energy consumption and prolong the network lifetime. However recent investigations point out that energy hole does not appear close to the sink and depends on some network factors such as the energy consumption model of sensor nodes.Theoretical study analysis is not provided in existing works to evaluate the emerging time and location of the energy holes as well as its evolution process.

## **II. RELATED WORK**

In wireless sensor networks, sensor nodes near to the sink node consume more energy than others because they are forced to relaying packet traffic towards for the sink and result in premature death of network resources. Energy hole is major problem for lifetime analysis in WSNs, because it can lead to early die of the network nodes and results into whole network failure. In existing system network is divided into a number of annulus whose widths are equal to the



# International Journal of Innovative Research in Computer and Communication Engineering

(An ISO 3297: 2007 Certified Organization)

Website: [www.ijirce.com](http://www.ijirce.com)

Vol. 4, Issue 12, December 2016

transmission range of the sensor nodes, and all the sensor nodes in the same bandwidth are assumed to die one by one. In existing WSN sensor nodes transmit the data packet via hop to hop communication. In that case all sensor nodes nearest node need to be spatially aware to take path towards transmission.

In [1], author defines the building area network for high-traffic advanced metering infrastructure in smart grid applications. Using multi-interface ZigBee, high-traffic communication in these building area networks (BANs), a multi-interface management framework is defined. This system provides the design engineer with seven recommendations for a generic MIZBAN design. Smart grid communication technology supports advanced metering infrastructure. The smart metering, AMI (advanced metering infrastructure) also facilitates utilities to perform demand response, and thus energy demand is reduced. Therefore various AMI pilot projects have been created around the world, e.g. in Australia, Japan, the United States, and Europe, and most of these are designed for individual homes. This system has benefits. The RTT measurement is only carried by sender and so no extra network traffic has been generated. RTT provides the updated transmission condition of the entire path because the path cost cannot be updated frequently because it can only be updated by performing route discovery, which may degrade the network performance. This system includes Channel selection algorithm and Interface selection algorithm.

In [2], author describes a ZigBee In-Patient Monitoring system embedded with a new ZigBee mobility management solution. This system enables ZigBee device mobility in a fixed ZigBee network. This system provides valuation which shows that the new algorithm offers a good efficiency, resulting in a low management cost. The system can save lives by supporting a panic button and can be used as a location discover service. A case study emphasis on the Princes of Wales Hospital in Hong Kong is enlisted and findings are given. This investigation reveals that the developed mobile solutions offer promising value-added services for many potential ZigBee applications.

In [3], author proposed the wireless sensor networks, the nodes have limited power supply and sometimes network lifetime expected as per the need. So the energy consumption and network lifetime are the key factors to achieve in WSN. This paper proposes an overlay, energy optimized, sensor network to extend the functional lifetime of an energy-intensive sensor network application. The overlay network consists of additional nodes that exposes recent advances in energy harvesting and wake-up radio technologies, coupled with an application specific, complementary and ultra-low power sensor. The experimental results and simulations prove that this study can ensure survivability of energy-inefficient sensor networks. This paper exploits these techniques to take advantage of the benefits of each and to extend the lifetime of the network while maintaining similar (or improved) security.

In [4], author defines WSN cluster based scheme used to reduce the energy consumption in WSN applications. Sometimes network lifetime is affected by unbalanced energy consumption in WSN due to many to one traffic pattern. In this system propose a Non-Uniform Node Distribution (NUND) scheme to improve the energy efficiency and network lifetime in cluster-based WSNs. Specifically, It first propose an analytic model to analyze the energy consumption and the network lifetime of the cluster-based WSNs. Based on the analysis results this system describes a node distribution algorithm to maximize the network lifetime along with a fixed number of sensor nodes in cluster-based WSNs.

In [5], author describes wireless sensor network the nodes near to sink node consumes more energy than the others as they are loaded with heavy traffic which results into energy hole or forming hotspots. In this system, three optimization algorithms are projected to mitigate hotspots and prolong network lifetime for adaptive Mary Phase Shift Keying based on wireless sensor networks where transport delay and reliability can be guaranteed. Based on the insight gained into the relationship between nodal data load and energy consumption in different regions the first algorithm (GlobalSame) can increase the network lifetime by selecting the optimal nodal transmission radius  $r$ , bit error rate  $\epsilon$  and transmission rate allocations in bits per symbol. The second algorithm (RingSame) can further improve network lifetime by comparison to the first algorithm. While the third algorithm NodeDiff can further improve the network lifetime by adopting different parameters of the same node for data packets received according to its distance to the sink.



# International Journal of Innovative Research in Computer and Communication Engineering

(An ISO 3297: 2007 Certified Organization)

Website: [www.ijirce.com](http://www.ijirce.com)

Vol. 4, Issue 12, December 2016

In [6], The author describes the network lifetime depends upon the design of network. In WSN, the most efficient way to maximize the lifetime of a wireless sensor network (WSN) is to provide energy to sensors they release their energy at the same time. The lifetime of a WSN as well as an optimal initial energy allocation are determined by a network design. The main contribution of the paper is to show that the lifetime of a WSN can be maximized by an optimal network design. We represent the network lifetime as a function of the number  $m$  of annuli and show that  $m$  has significant impact on network lifetime. The goal of this system is to increase lifetime of Wireless Sensor Network also including redundant sensor, nonuniform sensor distribution, aggregation and forwarding nodes for data transmission using routing algorithm.

In [7], author proposed system that represents the area near the sink nodes. The network lifetime is limited by heavy-traffic. This work attempts to improve the energy efficiency of the sink node to overall improvement of the network lifetime by considering a duty cycled WSN. studies carried out to evaluate the upper bounds of the network lifetime by considering (i) duty cycle, (ii) network coding and (iii) combinations of duty cycle and network coding. Energy efficiency of the bottleneck zone increases because more volume of data will be transmitted to the Sink with the same number of transmissions. This improves the overall lifetime of the network. Performance metrics such as packet delivery ratio and packet latency have also been investigated. The theoretical study and simulation results have been provided to show the efficacy of the proposed approach.

In [8], author defines wireless sensor networks variety of mission-critical applications, are comprised of sensor nodes with limited battery power. Improvement of energy efficiency and estimation of network lifetime are important issues in these energy constrained networks. This system present a probabilistic model for estimating the network lifetime of a sensor network. The traffic generation model is build up for unbalanced surfaces while combining the Elfessensing model and event generation model. A discrete radio model is considered in this system for better energy efficiency. Two different scenarios, such as, singlehop and multi-hop networks are analyzed with the proposed model. The likelihood of achieving the desired network lifetime with the proposed model is evaluated. Essential simulations are done taking the topology from real-sensor network testbeds. We also estimate the packet loss rates and the results also confirm the accuracy and energy efficiency of the proposed model.

In [9], author explains due to extended networks the problem of data gathering and sampling becomes critical in WSN. Increasing network size poses significant data collection challenges, for what concerns sampling and transmission coordination as well as network lifetime. To resolve these problems, in-network compression techniques without centralized coordination are becoming important solutions to extend lifetime. This system consider a scenario in which a large WSN, based on ZigBee protocol, is used for monitoring (e.g., building, industry, etc.). It propose a new algorithm for in-network compression aiming at longer network lifetime. This approach is fully distributed: each node autonomously takes a decision about the compression with respect to network size using datasets collected by a real-life deployment. An improved version of the algorithm is also introduced to take into account the energy spent in compression.

In [10], author proposes wireless sensor networks, event driven clustering approach used for analyzing the network lifetime is presented when events occur randomly over the network field. This system model the packet transmission rate of the sensors, using the theory of coverage processes and Voronoi tessellation. Then, the probability of achieving a given lifetime by individual sensors is found. This probability is then used to study the cluster lifetime. It finds an accurate approximation for the probability of achieving a desired lifetime by a cluster. The proposed study contains the effect of packet generation model, random deployment of sensors, dynamic cluster head assignment, data compression, and energy consumption model at the sensors.

### III. GOALS AND OBJECTIVE

In sensor networks, sensor nodes near to the sink node consume more energy than others because they are forced to relaying packet traffic towards for the sink and result in premature death of network resources. Energy hole is major problem for lifetime analysis in WSNs, because it can lead to early die of the network nodes. In existing system



# International Journal of Innovative Research in Computer and Communication Engineering

(An ISO 3297: 2007 Certified Organization)

Website: [www.ijirce.com](http://www.ijirce.com)

Vol. 4, Issue 12, December 2016

thenetwork is divided into a number of annulus whose widths are same to transmission range of the sensor nodes and all the sensor nodes in the same bandwidth are assumed to die one by one. In existing WSN sensor nodes transmit the data packet via hop to hop communication. In that case all sensor nodes nearest node need to spatially aware to take path towards transmission.

## IV. PROPOSED ALGORITHM

### 1. Network life time determination

**Input:** Network radius  $R$ , transmission radius  $r$ , node density of the network  $\rho$ , and other parameters.

**Output:** For each stage  $i$  and each node  $j$ , return the nodal traffic load  $P_j^{(i)}$  energy consumption,  $e_j^{(i)}$  as well as the energy transfer function and lifetime vector  $l$ .

1: Determine the traffic load and energy consumption of each node at stage  $S_0$ , i.e.

$[P_1^{(0)}, P_2^{(0)}, \dots, P_j^{(0)}, \dots, P_n^{(0)}]$  and  $[e_1^{(0)}, e_2^{(0)}, \dots, e_j^{(0)}, \dots, e_n^{(0)}]$ , according to Theorems 1 and 2;

2:  $i = 1$ ;

3: **While** the sink can receive data in a data period **do**

4: According to Corollary 1, calculate the lifetime  $l^{(i-1)}$  at stage  $S_{i-1}$ , and the  $i$ th batch of dead nodes region  $[u_i, u_i + \epsilon]$ ;

5: Determine the traffic load and energy consumption of the sensor nodes at stage  $S_i$ , i.e.,

$[P_1^{(i)}, P_2^{(i)}, \dots, P_j^{(i)}, \dots, P_n^{(i)}]$  and  $[e_1^{(i)}, e_2^{(i)}, \dots, e_j^{(i)}, \dots, e_n^{(i)}]$ , according to Theorems 3 and 4;

6:  $i = i + 1$ ;

7: **end while**

8: **return** the traffic load and energy consumption  $P_j^{(i)}$  and  $e_j^{(i)}$  (for each  $i$  and  $j$ ), and the network stage duration vector  $l^{(i)}$  (for each  $i$ ).

### 2. Determination of energy time and boundary of energy hole

**Input:** Network radius  $R$ , transmission radius  $r$ , node density of the network  $\rho$ , and other parameters.

**Output:** The energy hole boundary  $[d_{shole}, d_{ehole}]$  and emerging time  $t_h$ .

1: Run Algorithm 1 until there is a continuous dead ring whose width  $d$  satisfies  $d \geq r$ ;

2: The boundary of this dead region is the request  $[d_{shole}, d_{ehole}]$ ;

3: The lifetime at this network stage is the emerging time  $t_h$ ;

4: **return**  $[d_{shole}, d_{ehole}]$  and  $t_h$ .

## V. PROPOSED SYSTEM ARCHITECTURE

Proposed system represents an analytic model that determine the network lifetime. Network initialization is used to determine the network lifetime and energy hole in WSN. This system determines the traffic load, energy consumption, and lifetime of sensor nodes during the entire network lifetime. In the energy consumption and network lifetime analysis for WSNs, Most of them focus on the duration from network initialization to the time when the first node dies [i.e., first node died time (FNDT)], aiming to improve the network performances and optimize the FNDT. In addition to that we cluster the sensor node to mitigate energy consumption for data packet. By leveraging problem of security analytics of data sensor we accumulate node security by bridge protection. And node to node authentication which gives secure node communication for packet broadcasting.

### Explanation-

We define the network lifetime as the duration from the network initialization to the time when the network is disabled. For a data-gathering WSN, the network is generally disabled under the following two situations. One is that all the sensor nodes exhaust their energy and die. The other is that the sink cannot receive any data in a data period due to the energy hole partitioning the network, even if there are still a large number of alive nodes in the outer region of the energy hole. For simplification, we denote the network lifetime as ANDT and the time when the first node dies as FNDT. We describe the entire process of network lifetime in Fig. 1. Since the sensor nodes periodically send the sensed data to the sink in a data period, the network lifetime is slotted into a large number of data periods. We call the data periods in which at least a sensor node dies as death periods.



# International Journal of Innovative Research in Computer and Communication Engineering

(An ISO 3297: 2007 Certified Organization)

Website: [www.ijirccce.com](http://www.ijirccce.com)

Vol. 4, Issue 12, December 2016

## Advantages of Proposed System

1. Extend the lifetime analysis into energy harvesting WSNs.
2. Improve network security by node authentication.

## VI. CONCLUSION

Proposed system represents architecture to overcome the network traffic load, reduce energy consumption, and lifetime of sensor nodes in a data collection. In this system, we have evaluated the network lifetime under failed nodes, and analyzed the emerging time and location of energy hole, as well as its evolution process. In addition to this, two network characteristics have been found based on our analytic results, which can be leveraged to guide the WSN design and optimization. Our simulation results demonstrate that the proposed analytic model can estimate the network lifetime and energy hole evolution process within an error rate smaller than 5%. Finally, we have applied our analytic results to WSN routing. Proposed routing scheme is leads to results of efficiently balance the energy consumption and increase the network lifetime

## REFERENCES

- [1] Y. Tung et al., "The generic design of a high-traffic advanced metering infrastructure using zigbee," IEEE Trans. Ind. Informat., vol. 10, no. 1, pp. 836–844, Feb. 2014.
- [2] C. Tung et al., "A mobility enabled inpatient monitoring system using a zigbee medical sensor network," Sensors, vol. 14, no. 2, pp. 2397–2416, 2014.
- [3] M. Magno, D. Boyle, D. Brunelli, E. Popovici, and L. Benini, "Ensuring survivability of resource intensive sensor networks through ultra-low power overlays," IEEE Trans. Ind. Informat., vol. 10, no. 2, pp. 946–956, May 2014.
- [4] J. Ren, Y. Zhang, and X. Lin, "NUND: Non-uniform node distribution in cluster-based wireless sensor networks," KSII Trans. Internet Inf. Syst., vol. 8, no. 7, pp. 2302–2324, 2014.
- [5] A. Liu, D. Zhang, P. Zhang, G. Cui, and Z. Chen, "On mitigating hotspots to maximize network lifetime in multi-hop wireless sensor network with guaranteed transport delay and reliability," P2P Netw. Appl., vol. 7, no. 3, pp. 255–273, 2014.
- [6] K. Li, "Optimal number of annuli for maximizing the lifetime of sensor networks," J. Parallel Distrib. Comput., vol. 74, no. 1, pp. 1719–1729, 2014.
- [7] R. Rout and K. Ghosh, "Enhancement of lifetime using duty cycle and network coding in wireless sensor networks," IEEE Trans. WirelessCommun., vol. 12, no. 2, pp. 656–667, Feb. 2013.
- [8] A. Chakraborty, R. Rout, A. Chakrabarti, and S. Ghosh, "On network lifetime expectancy with realistic sensing and traffic generation model in wireless sensor networks," IEEE Sensors J., vol. 13, no. 7, pp. 2771–2779, Jul. 2013.
- [9] C. Caione, D. Brunelli, and L. Benini, "Distributed compressive sampling for lifetime optimization in dense wireless sensor networks," IEEE Trans.Ind.Informat., vol. 8, no. 1, pp. 30–40, Feb. 2012.
- [10] M. Noori and M. Ardakani, "Lifetime analysis of random event-driven clustered wireless sensor networks," IEEE Trans. Mobile Comput., vol. 10, no. 10, pp. 1448–1458, Oct. 2011.